

Ocean Surface Wave Optical Roughness – Innovative Measurement and Modeling

Johannes Gemmrich
Physics and Astronomy
University of Victoria
Victoria, BC, V8W 3P6, Canada;
Tel: 250-363-6448; gemmrich@uvic.ca

Award Number: N000140710015

LONG-TERM GOALS

I am part of a multi-institutional research team funded by the ONR-sponsored Radiance in a Dynamic Ocean (RaDyO) program. The primary research goals of the program are to (1) examine time-dependent oceanic radiance distribution in relation to dynamic surface boundary layer (SBL) processes; (2) construct a radiance-based SBL model; (3) validate the model with field observations; and (4) investigate the feasibility of inverting the model to yield SBL conditions. Our goals are to contribute innovative measurements, analyses and models of the sea surface roughness at length scales as small as a millimeter. This characterization includes microscale and whitecap breaking waves.

The members of the research team are

Michael Banner, School of Mathematics, UNSW, Sydney, Australia

Johannes Gemmrich, Physics and Astronomy, UVic, Victoria, Canada

Russel Morison, School of Mathematics, UNSW, Sydney, Australia

Howard Schultz, Computer Vision Laboratory, Computer Science Dept, U. Mass., Mass

Christopher Zappa, Lamont Doherty Earth Observatory, Palisades, NY

OBJECTIVES

Nonlinear interfacial roughness elements - sharp crested waves, breaking waves as well as the foam, subsurface bubbles and spray they produce, contribute substantially to the distortion of the optical transmission through the air-sea interface. These common surface roughness features occur on a wide range of length scales, from the dominant sea state down to capillary waves. Wave breaking signatures range from large whitecaps with their residual passive foam, down to the ubiquitous centimeter scale microscale breakers that do not entrain air. There is substantial complexity in the local wind-driven sea surface roughness microstructure, including very steep nonlinear wavelets and breakers. Traditional descriptors of sea surface roughness are scale-integrated statistical properties, such as significant wave height, mean squared slope (e.g. Cox and Munk, 1954) and breaking probability (e.g. Holthuijsen and Herbers, 1986). Subsequently, spectral characterisations of wave height, slope and curvature have been

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010	
4. TITLE AND SUBTITLE Ocean Surface Wave Optical Roughness - Innovative Measurement and Modeling				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Victoria, Physics and Astronomy, Victoria, BC, V8W 3P6, Canada,				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 6	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

measured, providing a scale resolution into Fourier modes for these geometrical sea roughness parameters. More recently, measurements of whitecap crest length spectral density (e.g. Phillips et al, 2001, Gemmrich et al., 2008) and microscale breaker crest length spectral density (e.g. Jessup and Phadnis, 2005) have been reported.

Our effort seeks to provide a more comprehensive description of the physical and optical roughness of the sea surface. We achieve this through the analysis of our suite of comprehensive sea surface roughness observational measurements within the RADYO field program. These measurements cover the fundamental optical distortion processes associated with the air-sea interface. In our data analysis, and complementary collaborative effort with RaDyO modelers, we are investigating both spectral and phase-resolved perspectives. These will allow refining the representation of surface wave distortion in present air-sea interfacial optical transmission models.

APPROACH

I am working within the larger team (listed above) measuring and characterizing the surface roughness. We build substantially on our accumulated expertise in sea surface processes and air-sea interaction. This team contributed the following components to the primary sea surface roughness data gathering effort in RaDyO:

- *polarization camera measurements* of the sea surface slope topography, down to capillary wave scales, of an approximately 1m x 1m patch of the sea surface (see Figure 1), captured at video rates. [Schultz, Zappa]
- *co-located and synchronous orthogonal 75 Hz linear scanning laser altimeter* data to provide spatio-temporal properties of the wave height field (resolved to O(0.5m) wavelengths) [Banner, Morison]
- *high resolution video imagery* to record whitecap data from two cameras, close range and broad field [Gemmrich]
- *fast response, infrared imagery* to quantify properties of the microscale breakers, and surface layer kinematics and vorticity [Zappa]
- *air-sea flux package including sonic anemometer* to characterize the near-surface wind speed and wind stress [Zappa]

The team's data analysis effort includes: detailed analyses of the slope field topography, including mean square slope, skewness and kurtosis; laser altimeter wave height and large scale wave slope data; statistics of whitecap properties, as well as statistical distributions of whitecap crest length density in different scale bands of propagation speed and similarly for the microscale breakers, as functions of the wind speed/stress and the underlying dominant sea state. Our contributions to the modeling effort focus on using RaDyO data to refine the sea surface roughness transfer function. This includes the representation of nonlinearity and breaking surface wave effects including bubbles, passive foam, active whitecap cover and spray, as well as micro-breakers.

WORK COMPLETED

My effort in FY10 has been primarily in the analysis of the surface video data obtained during the RaDyO field experiment off Hawaii, August 28 – September 16, 2009 as well as refinement to the data analysis for the field experiment in the Santa Barbara channel during September 4– 28, 2008. I also

participated in the ONR Optics review symposium (February 19 – 20, 2010) and the RaDyO workshop (June 1 – 3, 2010) where I presented a preliminary comparison of the results from our analysis of the RaDyO - Santa Barbara Channel video data and the RaDyO – Hawaii video data.

I continued work on the analysis techniques for characterizing breaking crests. Routines for image rectification and the extraction of length and propagation speed of breaking crests have been adopted for the Hawaii data set. Two approaches to establishing the breaking crest length distribution were evaluated: the spectral method (Thomson & Jessup, 2009) and the individual tracking method (Gemmrich et al, 2008). All final processing is based on the individual tracking method.

Of major significance to our group's effort was the deployment of our polarimeter in the RaDyO observational periods from Scripps Pier, from FLIP in the Santa Barbara channel and off Hawaii. Details on progress with this development are given in the companion ONR RaDyO Annual Reports by Schultz and Zappa.

RESULTS

Figure 1 below shows a schematic of the instrumentation deployed in the field experiments. Instrumentation and set-up were very similar in the Santa Barbara channel (2008) and the Hawaii (2009) field experiment. Banner/Morison deployed two orthogonal line scanning lidars. The lidars were positioned on the boom so that their intersection point was within the common footprint of the polarimetric (Schultz), infrared (Zappa) and visible (Gemmrich) imagery cameras which were measuring small-scale surface roughness features and breaking waves.




Figure 1. Schematic of the instrumentation set-up deployed from the R/P FLIP starboard boom during the Santa Barbara Channel and Hawaii experiments. The end of the boom was about 9m above the mean water level. The approximate field of view of the various instruments is shown. A second wide angle whitecap video camera was mounted on the crow's nest of R/P FLIP approximately 26m above the water level to image the larger whitecaps.

Zappa deployed his infrared/visible camera system and his environmental monitoring system (sonic anemometer, water vapor sensor, relative humidity/temperature probe, motion package, pyranometer and pyrgeometer). Gemmrich deployed 2 video visible imagery cameras. One camera was mounted on the main boom next to our other instrumentation packages, the second camera was mounted higher up to view larger scale breaking events. Schultz deployed an instrument package located on the boom that includes a polarimetric camera imaging the very small-scale waves. The individual data acquisition systems were synchronized and the various data sets can be interrelated to within 0.1 seconds. In this way breaking wave properties can be related to the phase of the underlying waves.

A wide range of conditions prevailed during the field experiment in Santa Barbara channel (September 4-28, 2008) where the wind speed U_{10} ranged from light and variable, up to 12 m/s. The scale of wave breaking ranged from micro breakers to small-scale breakers with air entrainment to breaking dominant waves with up to 2m wave height. Environmental conditions during the Hawaii experiment (Aug 28 – Sep 16, 2009) were less variable with a nearly fixed wind direction and wind speeds slowly fluctuating between 8 m/s and 12 m/s. Periods of comparable wind speeds resulted in significantly different wave fields (significant wave height, directionality, dominant period) at the two experimental sites.

These data are being analysed in terms of breaking crest length density, foam coverage and whitecap persistence.

Preliminary results on the breaking crest length distribution $\Lambda(c)$, obtained by the individual tracking method, are shown in Figure 2. All curves, for both data sets, show the maximum distribution to breaking crests in the intermediate to short wave range (small phase speeds). However, the absolute values and the slope of the curves vary significantly throughout the experiments. Generally, the slopes are less steep than the canonical value $\Lambda(c) \propto c^{-6}$ proposed by Phillips (1985) for the equilibrium range, which is based on assuming comparable importance of wind input, nonlinear spectral transfer and dissipation through breaking. The discrepancy seems to be somewhat larger for the coastal wave field in Santa Barbara channel. The slope decreases with increasing wave age, i.e. the relative importance of large scale breakers increases as the wave field develops. Thomson et al (2009) found the $\Lambda(c)$ -distribution to stratify according to the dominant steepness of the wave field $k_p H_s$. Here, we do not find such a dependency.

These breaking crest length distributions are solely based on video data. They are also compared to results from the infrared cameras (Zappa) and thereby extended to smaller wave scales. Breaking probabilities, momentum flux and energy dissipation can be extracted from these distributions (see Gemmrich *et al*, 2008).




Figure 2: Preliminary results on breaking crest length distributions $\Lambda(c)$ for the Santa Barbara channel experiment (left) and the Hawaii experiment (right). Each curve is based on a 20 minute video record. Colour coding represents the dominant steepness $k_p H_s$ (blue: high, red: low). The dashed line indicates a c^{-6} -dependence.

IMPACT/APPLICATIONS

This effort will provide a far more detailed characterization of the wind driven air-sea interface, including wave breaking (whitecaps and microscale breaking). This is needed to provide more complete parameterizations of these processes, which will improve the accuracy of ocean optical radiative transfer models and trans-interfacial image reconstruction techniques.

RELATED PROJECTS

The present project is related to the ONR project **WAVE ENERGY DISSIPATION AND THE DISTRIBUTION OF BREAKING CRESTS**, (ended December 2009), in which Andrew Jessup (APL, UW) was the principal investigator and I was a Co-PI (via subcontract). In this project we looked at breaking crest length distributions and co-located subsurface energy dissipation measurements in a strongly forced wave field in a lake and in Pudget Sound (Thomson *et al*, 2009; Gemmrich, 2010). While the wave scales in RaDyO and the lake/sound experiments are different, common aspects of the data analysis have been transferred to our RaDyO data sets.

REFERENCES

Cox, C.S. and Munk, W.H., 1954: Measurements of the roughness of the sea surface from photographs of the sun glitter. J. Opt. Soc. Am. 44, 838-850.

Gemmrich, J.R., M.L. Banner and C. Garrett, 2008: Spectrally resolved energy dissipation and momentum flux of breaking waves. *J. Phys. Oceanogr.* 38, 1296-1312.

Gemmrich, J.R, 2010: Strong turbulence in the wave crest region. *J. Phys. Oceanogr.* 40, 583 – 595

Holthuijsen, L.H., and T.H.C. Herbers, 1986: Statistics of breaking waves observed as whitecaps in the open sea, *J. Phys. Oceanogr.*, 16, 290-297.

Jessup, A.T. and K.R. Phadnis, 2005: Measurement of the geometric and kinematic properties of microscale breaking waves from infrared imagery using a PIV algorithm. *Meas. Sci. Technol.* 16, 1961-1969.

Phillips, O.M., 1985: Spectral and statistical properties of the equilibrium range in wind-generated gravity waves, *J. Fluid Mech.*, 156, 505-531.

Phillips, O.M., F.L. Posner and J.P. Hanson, 2001: High resolution radar measurements of the speed distribution of breaking events in wind-generated ocean waves: surface impulse and wave energy dissipation rates. *J. Phys. Oceanogr.*, 31, 450–460.

Thomson, J. and A. T. Jessup, 2009: A Fourier-Based Method for the Distribution of Breaking Crests from Video Observations. *J. Atm. Ocean. Tec.*, 26, 1663 – 1671.

Thomson, J., J. R. Gemmrich and A. T. Jessup, 2009: Energy dissipation and the spectral distribution of whitecaps. *Geophys. Res. Let.*, 36, L11601, doi:10.1029/2009GL038201

PUBLICATIONS

Gemmrich, J.R., M.L. Banner and C. Garrett, 2008: Spectrally resolved energy dissipation and momentum flux of breaking waves. *J. Phys. Oceanogr.* 38, 1296-1312. [published, refereed]

Gemmrich, J.R, 2010: Strong turbulence in the wave crest region. *J. Phys. Oceanogr.* 40, 583 – 595 [published, refereed]

Thomson, J., J. R. Gemmrich and A. T. Jessup, 2009: Energy dissipation and the spectral distribution of whitecaps. *Geophys. Res. Let.*, 36, L11601, doi:10.1029/2009GL038201 [published, refereed]

Zappa, C.J., M.L. Banner, H. Schultz, A. Corrada-Emmanuel, L.B. Wolff and J. Yalcin, 2008: Retrieval of Short Ocean Wave Slope Using Polarimetric Imaging. *Measurement Science and Technology*. *Measurement Science and Technology*, 19, 055503, pp 13, April 2008 [published, refereed].